

## presto Ceramic Spray

## Technical Information



presto Ceramic Spray is suitable for use on parts that are heavy duty or exposed to extremely high temperatures. The metal-free ceramic paste spray prevents long-term squeaking and creaking and is a highly effective lubricant, releasing agent and corrosion protection.

Application areas:

ABS and ASR brakes, lambda sensors and brake parts

Ord.-no: 157073

### Quality & properties

- Heat resistant and heavy duty
- Free of metal
- Excellent adhesion
- Non-conductive
- Contains ceramic particles, which avoid bonding
- Excellent thermo stability
- Make disassembly easier
- Resistant to chemicals and the effects of weather
- Water, salt, and weak acids and alkaline proof
- Free of heavy metals

### Physical & chemical data

- Base: Special resin
- Colourname: white
- Surfaces: ABS and ASR brakes, lambda sensors, brake parts
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 years
- Content: 400 ML

### How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Surface should be clean, dry and free of grease.
- Apply ceramic spray evenly and leave to dry.
- The specific properties are achieved after the solvent has evaporated (ca. 1 Minute).
- Make sure the friction areas are not sprayed!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of January 26, 2026** – This release replaces all eventually earlier issued versions.