

## MOTIP Waxcoating 1 I

## Technical Information



Prevent rust on your car with MOTIP Anti-Rust Waxcoating. Waxcoating is resistant to the weather, salt, water and weak acids and bases, has an excellent rust prevention and can be applied in thick layers.

**Ord.-no:** 00130, 00136

### Quality & properties

- To be applied with an UBC Spray-gun
- Excellent corrosion prevention
- Excellent adhesion
- Resistant to weather influences
- Resistant to salt, water and weak acids and bases
- Can be applied in thick layers

### Physical & chemical data

- Base: Wax
- Colourname:
  - transparent brown
  - black
- Smell: Characteristic
- Efficiency: 1,00 L – 2 - 3 m<sup>2</sup>
- Surfaces: Untreated metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point:
  - 37
  - 37 °C
- Storage stability:
  - 5 years
  - 1.5 years
- Content: 1,00 L

### How to use

Before use, carefully read the directions on the packaging and act accordingly. The can should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the can. Working pressure 4 to 5 bar. Apply the waxcoating in the desired layer thickness. After use, clean the spray-gun with white spirit.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of August 4, 2025** – This release replaces all eventually earlier issued versions.