

presto Copper Spray

Technical Information



presto Copper Spray is a high-quality thin liquid lubricant with a high copper content that is particularly suited to heat-resistant and heavy-duty parts.

Application areas:

- Lubricating battery contacts, brake parts, hinges and clutches
- Stopping disc brake pads from squeaking
- Protecting battery contacts and terminals
- On spark plugs, exhaust system joints and attachments and much more
- Not suitable for vehicles with ABS and ASR brake systems!

Ord.-no: 306383

Quality & properties

High thermo stability
From -40°C to +250°C; up to 1100°C in peak load
Excellent adhesion
Prevent wear and clamping of treated parts
Salt waterproof
Good corrosion protection
Prevents rust and oxidation
Chemical and weather resistant
Directed jet spray
Heat resistant

Physical & chemical data

Base: EP-2 Grease with copper
Colourname: copper colored
Smell: Characteristic
Surfaces: Battery contacts, brake parts, hinges, clutches
Minimum Working Temperature: 5 °C
Maximum Working Temperature: 30 °C
Flash point: n.a.
Storage stability: 10 years
Content: 400 ML

How to use

Bring the can to room temperature.
Operating temperature 5° to 30°C.
Shake can for 2 minutes before use.
Surface should be clean, dry and free of grease.
Apply evenly.
Optimum lubrication occurs once the solvent has evaporated (ca. 1 minute).
Screws and nuts should be sprayed before being screwed

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of January 26, 2026 – This release replaces all eventually earlier issued versions.